

NITE-LITE® SPECIFICATIONS



TECHNICAL INFORMATION

| | |
|--------------------|---|
| Fabric: | Vinyl-laminated polyester back-lit awning and sign fabric |
| Color: | Single-sided color/coated White backing for superior illumination |
| Top Coat: | Acrylic |
| Weight: | Approximately 16 oz. per square yard |
| Width: | 61 inches |
| Roll Size (Bolt): | 40 yards |
| Breaking Strength: | Warp 209 lbs./inch (931 N/in), Elongation 27% Fill 188 lbs./inch (836 N/in), Elongation 35% Test method ASTM D 5035 |
| Tear Strength: | Warp 25 lbs./inch (111 N/in) Fill 29 lbs./inch (131 N/in) Test method ASTM D 2261 |
| Flame Resistance: | Meets California Fire Marshall Title 19, paragraphs 1273.2 and 1237b Meets the requirements of NFPA 701 |

CLEANING INSTRUCTIONS

The following are our recommended cleaning instructions for Nite-Lite®:

- Rinse off loose dirt/dust with clean water.
- Mix mild soap/detergent with luke-warm water.
- Wash fabric with above mix using a soft cloth – preferably cotton.
- Rinse with clean water.
- **DO NOT** pressure-wash. This can damage the fabric.
- **DO NOT** use harsh chemicals. This could damage the protective acrylic top coat.